

Sky Air - R32 - Ceiling Mounted Cassette

Cassette air conditioner with 360° uniform airflow sets the standard

- > Circulation Airflow
- > Individual Airflow Direction Control
- > 360° Airflow
- > Selectable Airflow Pattern
- > Dual Sensors
- > Auto Airflow Function
- > Comfort and Energy Saving Preventing overcooling
- > Sensing sensor functions
- > Quick & Easy Installation
- > Easy Maintenance

Panel size is same for all models: makes it easy to maintain a neat appearance when multiple, units are installed.

		2 PK	2.5 PK	3 PK	4 PK	5 PK	6 PK
Model	Indoor	FCF50CVM4	FCF60CVM4	FCF71CVM4	FCF100CVM4	FCF125CVM4	FCF140CVM4
	Outdoor	RZF50CVM4	RZF60CVM4	RZF71CVM4	RZF100CVM4	RZF125CVM4	RZF140CVM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz					
Kapasitas	Btu/h	17,100 (10,900-19,100)	20,500 (10,900-20,500)	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,900)
	kW	5.0 (3.2-5.6)	6.0 (3.2-6.0)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)
Daya Listrik	KW	1.14	1.53	1.93	2.97	4.18	5.47
COP	W/W	4.39	3.92	3.68	3.37	2.99	2.56
Indoor	Dimensi (HxWxD)	mm 256x840x840		mm 256x840x840		mm 298x840x840	
	Berat Mesin	kg 22		kg 22		kg 24	
Outdoor	Dimensi (HxWxD)	mm 595x845x300		mm 595x845x300		mm 695x930x350	
	Berat Mesin	kg 41		kg 41		kg 48	
Ukuran Pipa	Cair	inch 3/8		inch 3/8		inch 3/8	
	Gas	inch 5/8		inch 5/8		inch 5/8	
Maksimal Pipa	Panjang	m 50		m 50		m 50	
	Tinggi	m 30		m 30		m 30	

		3 PK	4 PK	5 PK	6 PK
Model	Indoor	FCF71CVM4	FCF100CVM4	FCF125CVM4	FCF140CVM4
	Outdoor	RZF71CYM4	RZF100CYM4	RZF125CYM4	RZF140CYM4
Catu daya		Y: 380-415V, 3Ø, 50Hz / 380V, 3Ø, 60Hz			
Kapasitas	Btu/h	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,900)
	kW	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)
Daya Listrik	KW	1.93	2.97	4.18	5.47
COP	W/W	3.68	3.37	2.99	2.56
Indoor	Dimensi (HxWxD)	mm 256x840x840		mm 298x840x840	
	Berat Mesin	kg 22		kg 24	
Outdoor	Dimensi (HxWxD)	mm 695x930x350		mm 990x940x320	
	Berat Mesin	kg 48		kg 64	
Ukuran Pipa	Cair	inch 3/8		inch 3/8	
	Gas	inch 5/8		inch 5/8	
Maksimal Pipa	Panjang	m 50		m 50	
	Tinggi	m 30		m 30	

Sky Air - R-410A - Ceiling Mounted Cassette

Cassette air conditioner with 360° uniform airflow sets the standard

- > Avoids uneven temperature and discomfort caused by drafts
- > Comfort enhanced by Round Flow
- > Adapts easily to the installation space
- > Compact body and quiet operation
- > Quick and easy to install
- > Easier to maintain

Panel size is same for all models: makes it easy to maintain a neat appearance when multiple, units are installed.

		2 PK	2.5 PK	3 PK	4 PK	5 PK	6 PK
Model	Indoor	FCQ50KAVE4	FCQ60KAVE4	FCQ71KAVE4	FCQ100KAVE4	FCQ125KAVE4	FCQ140KAVE4
	Outdoor	RZR50MYM4	RZR60MYM4	RZR71MYM4	RZR100MYM4	RZR125MYM4	RZR140MYM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz			Y: 380-415V, 3Ø, 50Hz		
Kapasitas	Btu/h	17,100 (7,900-19,100)	20,500 (8,900-21,500)	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,600)
	kW	5.0 (2.3-5.6)	6.0 (2.6-6.3)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.4)
Daya Listrik	KW	1.24	1.58	1.99	2.78	4.31	5.62
COP	W/W	4.03	3.80	3.57	3.60	2.90	2.49
Indoor	Dimensi (HxWxD)	mm 256x840x840		mm 256x840x840		mm 298x840x840	
	Berat Mesin	kg 21		kg 21		kg 24	
Outdoor	Dimensi (HxWxD)	mm 595x845x300		mm 595x845x300		mm 990x940x320	
	Berat Mesin	kg 43		kg 43		kg 73	
Ukuran Pipa	Cair	inch 3/8		inch 3/8		inch 3/8	
	Gas	inch 5/8		inch 5/8		inch 5/8	
Maksimal Pipa	Panjang	m 50		m 50		m 50	
	Tinggi	m 30		m 30		m 30	

		6 PK	5 PK	6 PK
Model	Indoor	FCQ140KAVE4	FCQ125KAVE4	FCQ140KAVE4
	Outdoor	RZR140MYM4	RZR125LUY14	RZR140LUY14
Catu daya		Y: 380-415V, 3Ø, 50Hz		
Kapasitas	Btu/h	47,800 (21,200-52,600)	42,700 (19,500-47,800)	47,800 (21,200-52,600)
	kW	14.0 (6.2-15.4)	12.5 (5.7-14.0)	14.0 (6.2-15.4)
Daya Listrik	KW	5.62	3.68	4.91

COP		W/W	2.49	3.40	2.85
Indoor	Dimensi (HxWxD)	mm	298x840x840		
	Berat Mesin	kg	24		
Outdoor	Dimensi (HxWxD)	mm	990x940x320	1,170x900x320	
	Berat Mesin	kg	73	97	
Ukuran Pipa	Cair	inch	3/8		
	Gas	inch	5/8		
Maksimal Pipa	Panjang	m	50		
	Tinggi	m	30		