

Sky Air R32 - Ceiling Suspended

Comfortable airflow travels throughout the room

- > Stylish Model
- > Suitable for high ceilings
- > Quiet operation Installation flexibility for freedom of design
- > Flexible Installation
- > Easy Maintenance

		2 PK	2.5 PK	3 PK	4 PK	5 PK	6 PK
Model	Indoor	FHA50BVM4	FHA60BVM4	FHA71BVM4	FHA100BVM4	FHA125BVM4	FHA140BVM4
	Outdoor	RZF50CYM4	RZF60CYM4	RZF71CYM4	RZF100CYM4	RZF125CYM4	RZF140CYM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz					
Kapasitas	Btu/h	17,100 (10,900-19,100)	20,500 (10,900-20,500)	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,900)
	kW	5.0 (3.2-5.6)	6.0 (3.2-6.0)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)
Daya Listrik	KW	1.20	1.53	2.30	3.24	4.29	5.40
COP	W/W	4.17	3.92	3.09	3.09	2.91	2.59
Indoor	Dimensi (HxWxD)	235x960x690		235x1,270x690	235x1,590x690		
	Berat Mesin	25		32	38		
Outdoor	Dimensi (HxWxD)	595x845x300		595x845x300	695x930x350	990x940x320	
	Berat Mesin	41		41	48	64	
Ukuran Pipa	Cair	3/8		3/8			
	Gas	5/8		5/8			
Maksimal Pipa	Panjang	50		50			
	Tinggi	30		30			

		3 PK	4 PK	5 PK	6 PK
Model	Indoor	FHA71BVM4	FHA100BVM4	FHA125BVM4	FHA140BVM4
	Outdoor	RZF71CYM4	RZF100CYM4	RZF125CYM4	RZF140CYM4
Catu daya		Y: 380-415V, 3Ø, 50Hz / 380V, 3Ø, 60Hz			
Kapasitas	Btu/h	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,900)
	kW	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)
Daya Listrik	KW	2.30	3.24	4.29	5.40
COP	W/W	3.09	3.09	2.91	2.59
Indoor	Dimensi (HxWxD)	235x1,270x690		235x1,590x690	
	Berat Mesin	32		38	
Outdoor	Dimensi (HxWxD)	695x845x300		695x930x350	990x940x320
	Berat Mesin	48		64	
Ukuran Pipa	Cair	3/8			
	Gas	5/8			
Maksimal Pipa	Panjang	50			
	Tinggi	30			

Sky Air R-410A - Ceiling Suspended

Cassette air conditioner with 360° uniform airflow sets the standard

- > Avoids uneven temperature and discomfort caused by drafts
 - > Comfort enhanced by Round Flow
 - > Adapts easily to the installation space
 - > Compact body and quiet operation
 - > Quick and easy to install
 - > Easier to maintain
- Panel size is same for all models: makes it easy to maintain a neat appearance when multiple, units are installed.

		1.5 PK	2 PK	2.5 PK	3PK	4 PK	5 PK
Model	Indoor	FHQ35BV1B4	FHQ50DAVM4	FHQ60DAVM4	FHQ71DAVM4	FHQ100DAVM4	FHQ125DAVM4
	Outdoor	RKS35AVMG4	RZR50MVM4	RZR60MVM4	RZR71MVM4	RZR100MYM4	RZR125MYM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz				Y: 380-415V, 3Ø, 50Hz	
Kapasitas	Btu/h	11,600 (4,100-12,600)	17,100 (7,900-19,100)	20,500 (8,900-21,500)	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)
	kW	3.4 (1.2-3.7)	5.0 (2.3-5.6)	6.0 (2.6-6.3)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)
Daya Listrik	KW	1.05	1.24	1.58	2.37	3.03	4.42
COP	W/W	3.24	4.03	3.80	3.00	3.30	2.83
Indoor	Dimensi (HxWxD)	195x960x680	235x960x690		235x1,270x690	235x1,590x690	
	Berat Mesin	24	25		32	38	
Outdoor	Dimensi (HxWxD)	550x765x285	595x845x300		595x845x300	990x940x320	
	Berat Mesin	34	43		43	73	
Ukuran Pipa	Cair	1/4	3/8		3/8		
	Gas	3/8	5/8		5/8		
Maksimal Pipa	Panjang	20	50		50		
	Tinggi	15	30		30		

		6 PK	5 PK	6 PK
Model	Indoor	FHQ140DAVM4	FHQ125DAVM4	FHQ140DAVM4
	Outdoor	RZR140MYM4	RZR125LUY14	RZR140LUY14
Catu daya		Y: 380-415V, 3Ø, 50Hz		
Kapasitas	Btu/h	47,800 (21,200-52,600)	42,700 (19,500-47,800)	47,800 (21,200-52,600)
	kW	14.0 (6.2-15.4)	12.5 (5.7-14.0)	14.0 (6.2-15.4)
Daya Listrik	KW	5.55	4.55	4.68
COP	W/W	2.52	3.12	2.84
Indoor	Dimensi (HxWxD)	235x1,590x690		
	Berat Mesin	38		
Outdoor	Dimensi (HxWxD)	990x940x320	1,170x900x320	

Output	Berat Mesin	kg	73	97
Ukuran Pipa	Cair	inch	3/8	
	Gas	inch	5/8	
Maksimal Pipa	Panjang	m	50	
	Tinggi	m	30	