

## Sky Air R32 - Ceiling Mounted Duct Middle Standard

### Thinner design allows greater installation flexibility

- > Design & Installation Flexibility
- > Switchable fan Speed
- > Silver ion anti-bacterial drain pan
- > High Efficiency
- > Easy Maintenance

		2 PK	2.5 PK	3 PK	4 PK	5 PK	6 PK
Model	Indoor	FBA50BVM4	FBA60BVM4	FBA71BVM4	FBA100BVM4	FBA125BVM4	FBA140BVM4
	Outdoor	RZF50CYM4	RZF60CYM4	RZF71CYM4	RZF100CYM4	RZF125CYM4	RZF140CYM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz					
Kapasitas	Btu/h	17,100 (10,900-19,100)	20,500 (10,900-20,500)	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,900)
	kW	5.0 (3.2-5.6)	6.0 (3.2-6.0)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)
Daya Listrik	KW	1.35	1.64	2.15	3.01	4.44	5.69
COP	W/W	3.70	3.66	3.30	3.32	2.82	2.46
Indoor	Dimensi (HxWxD)	245x1,000x800		245x1,000x800	245x1,400x800		
	Berat Mesin	37		37	47		
Outdoor	Dimensi (HxWxD)	595x845x300		595x845x300	695x930x350	990x940x320	
	Berat Mesin	41		41	48	64	
Ukuran Pipa	Cair	3/8		3/8			
	Gas	5/8		5/8			
Maksimal Pipa	Panjang	50		50			
	Tinggi	30		30			

		3 PK	4 PK	5 PK	6 PK
Model	Indoor	FBA71BVM4	FBA100BVM4	FBA125BVM4	FBA140BVM4
	Outdoor	RZF71CYM4	RZF100CYM4	RZF125CYM4	RZF140CYM4
Catu daya		Y: 380-415V, 3Ø, 50Hz / 380V, 3Ø, 60Hz			
Kapasitas	Btu/h	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,900)
	kW	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)
Daya Listrik	KW	2.15	3.01	4.44	5.69
COP	W/W	3.30	3.32	2.82	2.46
Indoor	Dimensi (HxWxD)	245x1,000x800		245x1,400x800	
	Berat Mesin	37		47	
Outdoor	Dimensi (HxWxD)	695x930x350		990x940x320	
	Berat Mesin	48		64	
Ukuran Pipa	Cair	3/8			
	Gas	5/8			
Maksimal Pipa	Panjang	50			
	Tinggi	30			

## Sky Air R-410A - Duct Connection Middle & High

### Cassette air conditioner with 360° uniform airflow sets the standard

- > Avoids uneven temperature and discomfort caused by drafts
  - > Comfort enhanced by Round Flow
  - > Adapts easily to the installation space
  - > Compact body and quiet operation
  - > Quick and easy to install
  - > Easier to maintain
- Panel size is same for all models: makes it easy to maintain a neat appearance when multiple, units are installed.

		2 PK	2.5 PK	3PK	4 PK	5 PK	6 PK
Model	Indoor	FBQ50EVE4	FBQ60EVE4	FBQ71EVE4	FBQ100EVE4	FBQ125EVE4	FBQ140EVE4
	Outdoor	RZR50MYM4	RZR60MYM4	RZR71MYM4	RZR100MYM4	RZR125MYM4	RZR140MYM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz			Y: 380-415V, 3Ø, 50Hz		
Kapasitas	Btu/h	17,100 (7,900-19,100)	20,500 (8,900-21,500)	24,200 (10,900-27,300)	34,100 (17,100-38,200)	42,700 (19,500-47,800)	47,800 (21,200-52,600)
	kW	5.0 (2.3-5.6)	6.0 (2.6-6.3)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.4)
Daya Listrik	KW	1.39	1.69	2.22	2.82	4.58	5.85
COP	W/W	3.60	3.56	3.20	3.55	2.73	2.39
Indoor	Dimensi (HxWxD)	245x1,000x800		245x1,000x800	245x1,400x800		245x1,400x800
	Berat Mesin	37		37	47		47
Outdoor	Dimensi (HxWxD)	595x845x300		595x845x300	990x940x320		990x940x320
	Berat Mesin	43		43	73		73
Ukuran Pipa	Cair	3/8		3/8			3/8
	Gas	5/8		5/8			5/8
Maksimal Pipa	Panjang	50		50			50
	Tinggi	30		30			30

		5 PK	6 PK
Model	Indoor	FBQ125EVE4	FBQ140EVE4
	Outdoor	RZR125LUY14	RZR140LUY14
Catu daya		Y: 380-415V, 3Ø, 50Hz	
Kapasitas	Btu/h	42,700 (19,500-47,800)	47,800 (21,200-52,600)
	kW	12.5 (5.7-14.0)	14.0 (6.2-15.4)
Daya Listrik	KW	3.73	4.71
COP	W/W	3.35	2.97
Indoor	Dimensi (HxWxD)	245x1,400x800	
	Berat Mesin	47	
Outdoor	Dimensi (HxWxD)	1,170x900x320	

Ukuran	Berat Mesin	kg	97
Ukuran Pipa	Cair	inch	3/8
	Gas	inch	5/8
Maksimal Pipa	Panjang	m	50
	Tinggi	m	30