

Sky Air R32 - Floor Standing

New airflow control for more comfort

- > Comfortable airflow control
- > High Efficiency
- > Easy Maintenance
- > Easy Installation
- > Wireless remote controller

Model		Indoor		2 PK	2.5 PK	3 PK	4 PK	5 PK	6 PK
		Outdoor		FVA50AMVM	FVA60AMVM	FVA71AMVM	FVA100AMVM	FVA125AMVM	FVA140AMVM
				RZF50CVM4	RZF60CVM4	RZF71CVM4	RZF100CVM4	RZF125CVM4	RZF140CVM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz							
Kapasitas		Btu/h	34,100		34,100	24,200	34,100	42,700	47,800
			(17,100-38,200)		(17,100-38,200)	(10,900-27,300)	(17,100-38,200)	(19,500-47,800)	(21,200-52,900)
		kW	10.0 (5.0-11.2)		10.0 (5.0-11.2)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)
Daya Listrik		KW	3.6		3.6	2.51	3.48	4.48	5.71
COP		W/W	2.78		2.78	2.83	2.87	2.99	14.0
Indoor	Dimensi (HxWxD)	mm	340x1,200x240			1,850x600x270	1,850x600x350	1,850x600x350	1,850x600x350
	Berat Mesin	kg	17			39	47		
Outdoor	Dimensi (HxWxD)	mm	695x930x350			595x845x300	695x930x350	990x940x320	
	Berat Mesin	kg	48			41	48	64	
Ukuran Pipa		Cair	inch		3/8		3/8		
		Gas	inch		5/8		5/8		
Maksimal Pipa		Panjang	m		50		50		
		Tinggi	m		30		30		

Model		Indoor		3 PK	4 PK	5 PK	6 PK	
		Outdoor		FVA71AMVM	FVA100AMVM	FVA125AMVM	FVA140AMVM	
				RZF71CYM4	RZF100CYM4	RZF125CYM4	RZF140CYM4	
Catu daya		Y: 380-415V, 3Ø, 50Hz / 380V, 3Ø, 60Hz						
Kapasitas		Btu/h	24,200		34,100	42,700	47,800	
			(10,900-27,300)		(17,100-38,200)	(19,500-47,800)	(21,200-52,900)	
		kW	7.1 (3.2-8.0)		10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.5)	
Daya Listrik		KW	2.51		3.48	4.48	5.71	
COP		W/W	2.83		2.87	2.79	2.45	
Indoor	Dimensi (HxWxD)	mm	1,850x600x270		1,850x600x350	1,850x600x350	1,850x600x350	
	Berat Mesin	kg	39		47	47	47	
Outdoor	Dimensi (HxWxD)	mm	595x845x300		695x930x350	990x940x320	990x940x320	
	Berat Mesin	kg	48		48	64	64	
Ukuran Pipa		Cair	inch		3/8		3/8	
		Gas	inch		5/8		5/8	
Maksimal Pipa		Panjang	m		50		50	
		Tinggi	m		30		30	

Sky Air R-410A - Floor Standing

Cassette air conditioner with 360° uniform airflow sets the standard

- > Avoids uneven temperature and discomfort caused by drafts
 - > Comfort enhanced by Round Flow
 - > Adapts easily to the installation space
 - > Compact body and quiet operation
 - > Quick and easy to install
 - > Easier to maintain
- Panel size is same for all models: makes it easy to maintain a neat appearance when multiple, units are installed.

Model		Indoor		2 PK	2.5 PK	3PK	4 PK	5 PK	6 PK
		Outdoor		FVQ50CVE4	FVQ60CVE4	FVQ71CVEB4	FVQ100CVEB4	FVQ125CVEB4	FVQ140CVEB4
				RZR50MVM4	RZR60MVM4	RZR71MVM4	RZR100MYM4	RZR125MYM4	RZR140MYM4
Catu daya		V: 220-240V, 1Ø, 50Hz / 220-230V, 1Ø, 60Hz				Y: 380-415V, 3Ø, 50Hz			
Kapasitas		Btu/h	17,100		20,500	24,200	34,100	42,700	47,800
			(7,900-19,100)		(8,900-21,500)	(10,900-27,300)	(17,100-38,200)	(19,500-47,800)	(21,200-52,600)
		kW	5.0 (2.3-5.6)		6.0 (2.6-6.3)	7.1 (3.2-8.0)	10.0 (5.0-11.2)	12.5 (5.7-14.0)	14.0 (6.2-15.4)
Daya Listrik		KW	1.27		1.84	2.58	3.28	4.62	5.89
COP		W/W	3.94		3.26	2.75	3.05	2.71	2.38
Indoor	Dimensi (HxWxD)	mm	1,850x600x270						
	Berat Mesin	kg	39		39	47			
Outdoor	Dimensi (HxWxD)	mm	595x845x300		595x845x300	990x940x320			
	Berat Mesin	kg	43		43	73			
Ukuran Pipa		Cair	inch		3/8		3/8		
		Gas	inch		5/8		5/8		
Maksimal Pipa		Panjang	m		50		50		
		Tinggi	m		30		30		

Model		Indoor		4 PK	5 PK	6 PK
		Outdoor		FVQ100CVEB4	FVQ125CVEB4	FVQ140CVEB4
				RZR100LUY14	RZR125LUY14	RZR140LUY14
Catu daya		Y: 380-415V, 3Ø, 50Hz				
Kapasitas		Btu/h	34,100		42,700	46,100
			(17,100-38,200)		(19,500-47,800)	(21,200-52,600)
		kW	10.0 (5.0-11.2)		12.5 (5.7-14.0)	13.5 (6.2-15.4)
Daya Listrik		KW	3.28		4.39	5.40
COP		W/W	3.05		2.85	2.59
Indoor	Dimensi (HxWxD)	mm	1,850x600x350			
	Berat Mesin	kg	47			
Outdoor	Dimensi (HxWxD)	mm	1,170x900x320			
	Berat Mesin	kg	92		97	

Ukuran Pipa	Cair	inch	3/8
	Gas	inch	5/8
Maksimal Pipa	Panjang	m	50
	Tinggi	m	30